

# Scotch® Tear Tape 8626



## Technical Data

May, 2003

### Product Description

Scotch® Tear Tape 8626 is designed for use as the easy-opening device on medium- to heavy-weight corrugated fiberboard packaging materials. Typical easy-opening applications for Scotch® Tape 8626 include: overnight courier boxes; audio/video/CD/book mailers; printed boxes used in the retail market for such items as electronics, toys, medical, computers, and clothing; and shipping boxes used by catalogs and “mail order” retailers, who want to avoid product damage from knives, razor blades and scissors used to open the packages.

### Construction

Backing	Adhesive	Reinforcement	Backing Color
Tensitized polypropylene	Pressure sensitive synthetic rubber resin	None	Ivory

### Typical Physical Properties\*

**Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.**

		ASTM Test Method
Adhesion to Steel:	75 oz./in. width (82 N/100 mm width)	D-3330
Tensile Strength:	220 lbs./in. width (3850 N/100 mm width)	D-3759
Elongation at Break:	30%	D-3759
Total Thickness:	6.2 mil (.157 mm)	D-3652

\*Based on limited production. As sufficient production data is gathered, a revised data sheet will be issued.

### Available Sizes

Available Widths	Available Lengths	Outside Diameter
Standard Widths: .1875 in. (4.75 mm)	20,000 yds. (18,280 m)	15.5 in.
Core Size (ID): 6 in. (152.4 mm)		
Core Width: 7 in. (177.8 mm)		

### Storage Conditions

Store behind present stock. Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40-50% relative humidity are recommended. Rotate your stock.

# Scotch® Tear Tape

8626

---

## For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit [www.3M.com/packaging](http://www.3M.com/packaging). Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

---

## Important Notice

3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's application.

---

## Limitation of Remedies and Liability

If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.

**ISO 9002**

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.

**3M**

Industrial Business  
Industrial Adhesives and Tapes Division  
3M Center, Building 21-1W-10, 900 Bush Avenue  
St. Paul, MN 55144-1000



Recycled Paper  
40% pre-consumer  
10% post-consumer

Printed in U.S.A.  
©3M 2003 70-0710-0291-2 (5/03)