

# 3M

## ScotchPad™

### Repositionable Tape Pad

#### 802

Technical Data

May, 2003

**Product Description** 3M™ ScotchPad™ Repositionable Tape Pad 802 are pre-cut pads composed of lined sheets of low adhesion tape and can be easily applied to a surface, removed, and reapplied to another surface. The conformable acetate backing and Post-it® adhesive in these sheets give excellent long aging characteristics. The matte surface can be written on.

Construction	Backing	Adhesive	Colors
	Acetate	Post-it® low adhesion adhesive	Clear

**Typical Physical Properties** **Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.**

		ASTM Test Method
Adhesion to Steel:	1.5 oz./in. width (1.6 N/100 mm width)	D-3330
Tensile Strength:	15 lbs./in. width (265 N/100 mm width)	D-3759
Elongation at Break:	15%	D-3759
Total Thickness:	2.0 mil (0.051 mm)	D-3652
Adhesion to Neenah Bond Paper:	3.0 oz./in. width (3.3 N/100 mm width)	D-3654

- Features**
- Paper liner at one end of sheet.
  - Cleanly removable from most surfaces.
  - Will not yellow or stain.
  - Will not dry out, harden, or become brittle.
  - Matte surface can be written on with pen, pencil, and other writing implements.
  - Almost invisible appearance when applied.
  - Labor saving and portable.
  - Will hold a note or label which can be moved or peeled away from the tape without damage.
  - Corrections, directions, changes can be noted on surface.
  - When copies are made the tape will not shadow.
  - Can be read through easily.
  - Will stay supple and protect the surface below it from moisture and aging.

**Available Sizes** Standard Width: 4 in. x 6 in.  
25 sheets per pad

# 3M™ ScotchPad™ Repositionable Tape Pad 802

---

**Application Techniques** 3M™ ScotchPad™ Repositionable Tape Pad 802 sheets will remove cleanly from most office papers, manila folders, painted wall board, wallpaper, finished woods, metals and plastics, but test the product before using. Avoid applications on lacquered finishes, blackboards, CIBA chrome photographic paper, lexan plastic and leather, because adhesive will shred on these surfaces. Removal is possible with a dry tissue, soft eraser, window cleaner or rubbing alcohol.

---

**Storage Conditions** Storage in a clean, dry place in 40-50% relative humidity and temperature of 40-80°F (4-26°C) is recommended.

---

**For Additional Information** To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit [www.3M.com/packaging](http://www.3M.com/packaging). Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

---

**Important Notice** 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's application.

---

**Limitation of Remedies and Liability** If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.



**Industrial Business  
Industrial Adhesives and Tapes Division**  
3M Center, Building 21-1W-10, 900 Bush Avenue  
St. Paul, MN 55144-1000



*Recycled Paper  
40% pre-consumer  
10% post-consumer*

Printed in U.S.A.  
©3M 2003 70-0710-0244-1 (5/03)