


March, 2017

3M™ Extra Heavy Duty Duct Tape 6969

Product Description

3M™ Extra Heavy Duty Duct Tape 6969 is an industrial strength duct tape composed of an abrasion resistant, polyethylene film over a dense cloth scrim water proof backing with an aggressive rubber adhesive used for demanding duct tape applications.



Product Features

- Offers industrial strength backing, easy tear, and abrasion resistance.
- Olive color is useful for military applications.
- Low tack roll edges (48 mm) so edges stay cleaner for less surface contamination, and less waste.
- Individual roll wrap (48 mm) that preserves integrity of the roll for less waste.
- Polyethylene coated cloth scrim that resists moisture to prolong tape bond.
- Rubber adhesive that adheres aggressively to most surfaces for good holding power.

3M™ Extra Heavy Duty Duct Tape 6969

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Color	Black, Olive, Silver		
Total Tape Thickness	0.25 mm	10 mil	ASTM D3652
Backing	Polyethylene film over cloth scrim		
Adhesive	Rubber		

Typical Performance Characteristics

Property	Values		Method	Substrate	Notes
Peel Adhesion	5.6 N/cm	51 oz/in	ASTM D3330	Stainless Steel	
Tensile Strength	59.5 N/cm	544 oz/in	ASTM D3759		
Elongation at Break	16 %		ASTM D3759		
Temperature Use Range	Up to 93 °C	Up to 200 °F			
Flame Spread Index	0		ASTM E84		UL-723, NFPA 255, and UBC 8-1 are publications of the same test method.
Smoke Developed Index	5		ASTM E84		UL-723, NFPA 255, and UBC 8-1 are publications of the same test method.

3M™ Extra Heavy Duty Duct Tape 6969

Available Sizes

Property	Values	
Standard Roll Length	54.8 m	60 yd
Standard Width	48, 72 mm	1.89, 2.83 in

Handling/Application Information

Application Ideas

- A good choice of tape for HVAC, industrial, construction, abatement, trucking and automotive industries.
- Reinforcing, bundling, moisture proofing, sealing, splicing, temporary repair.
- Hanging poly, repairing and splicing tarps, seaming.

Storage and Shelf Life

Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton. To obtain best performance, use this product within 18 months from date of manufacture.

Trademarks

3M is a trademark of 3M Company.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all-3m-products/~/~3M-Extra-Heavy-Duty-Duct-Tape-6969?N=5002385+3293241050&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=6969

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Extra Heavy Duty Duct Tape 6969

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

3M™ Extra Heavy Duty Duct Tape 6969



3M United States
3M Center
St. Paul, MN 55144-1000
800-362-3550
www.3M.com

Please recycle.
© 3M 2020. All Rights Reserved.

The brands listed above are trademarks of 3M