

February, 2017

3M™ Polyester Protective Tape 335

Product Description

3M™ Polyester Protective Tape 335 is a thin polyester tape with a low tack adhesive. Designed to protect finished surfaces from light abrasion, nicks and scratches during production, packing, shipping and installation.

Product Features

- Low tack rubber adhesive adheres to a wide variety of surfaces with minimal adhesion build-up and clean removal when finished.
- Provides excellent abrasion, tear, scratch, puncture and moisture resistance to help protect surfaces.
- Extensible, abrasion resistant backing is ideal for forming operations.
- Pink color of the 3M tape 335 provides easy visibility for either application or removal, providing quick identification of protected versus unprotected areas.
- These tapes can be used for extended periods of time up to 150°F (66°C) and for 30 minutes or less at 250°F (121°C).



Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Color	Pink		
Total Tape Thickness	0.04 mm	1.5 mil	ASTM D3652
Backing Thickness	0.02 mm	0.94 mil	ASTM D3652
Backing	Polyester		
Adhesive	Rubber		

Typical Performance Characteristics

Property	Values		Method	Substrate
Peel Adhesion	0.235 N/cm	2.15 oz/in	ASTM D3330	Stainless Steel
Tensile Strength	43.8 N/cm	400 oz/in	ASTM D3759	
Elongation at Break	115 %		ASTM D3759	

Temperature Use Range		Test Condition
Up to 66 °C	Up to 150 °F	Extended Periods
Up to 121 °C	Up to 250 °F	Up to 30 min

Property: Temperature Use Range

Available Sizes

Property	Values	
Standard Roll Length	131.6 m	144 yd

Handling/Application Information

Application Ideas

- Protection from fumes and splash during plating processes on the upper portion of printed wiring boards.
- Protection of polished stainless steel and aluminum in fabrication, shipping, and storage.
- Protection of nameplates and instrument panels during shipping and installation.
- Protection of finished non-metallic surfaces.
- Protection of non-image side of inner layers of multilayer printed wiring boards.

3M™ Polyester Protective Tape 335

Handling/Application Information (continued)

Application Techniques

- Adhesion levels can increase from any of the following conditions:
 - Extended exposure to direct sunlight
 - High stacking pressures
 - Extended application to copper bearing surfaces

Storage and Shelf Life

Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton. To obtain best performance, use this product within 12 months from date of manufacture.

Trademarks

3M is a trademark of 3M Company.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all-3m-products/-/3M-Polyester-Protective-Tape-335?N=5002385+3293242598&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=335

Family Group

	335	336
Color	Pink	Transparent
Total Tape Thickness (mm)	0.04	0.04
Backing Thickness (mm)	0.02	0.02
Backing	Polyester	Polyester
Adhesive	Rubber	Rubber
Tensile Strength (N/cm)	43.8	43.8

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

