

February, 2003

3M™ ScotchPad™ Label Protection Tape Pads 822

Product Description

3M™ ScotchPad™ Label Protection Tape Pad 822 is a pre-cut pad formed with layered high-performance tape sheets featuring durable 3M™ Scotchpro™ polypropylene film backing that is strong, conformable, and resistant to impact shock. Tape sheets are coated with an aggressive adhesive to provide excellent adhesion to many types of surfaces. Each piece of tape is coupled with a liner material for easy handling and dispensing, without the need for a dispenser. Tape sheets are used for repairing broken packages, for label protection, industrial covering applications, and protection of surfaces in manufacturing processes. Tuck-in flap boxes are securely closed with these tape sheets.

Product Features

- Individual liner tabs.
- Pre-cut individual sheets layered 25 to a back sheet.
- Strong and long aging.
- Abrasion and weather resistance.
- Easy removal of a single sheet.
- Easy removal of liner upon application.
- Portable and light-weight.
- Convenient and space saving.
- Dust-free adhesive surface.
- Exact replication.
- Helps prevent labels from being scuffed off.
- Guards information against weather damage.
- High visibility of label legend.
- Helps prevent labels from yellowing or drying out during normal label life.
- Holds tight to most cartons and containers.
- Protects and allows for bar code read.
- Fast and easy to use.
- Proper positioning and wrinkle-free application possible.
- Quick, efficient usage.
- Easy to store in pockets, drawers, and on desktops.



3M™ ScotchPad™ Label Protection Tape Pads 822

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Available Formats

25 Sheets Per Pad
40 Pads per Carton
5 Cartons per Case
200 Pads per Case
5000 Applications per Case

Property	Values		Method
Color	Transparent		
Total Tape Thickness	0.079 mm	3.1 mil	ASTM D3652
Backing Thickness	0.05 mm	2 mil	ASTM D3652
Backing	Biaxially oriented 3M™ Scotchpro™ polypropylene film		
Adhesive	*Pressure sensitive rubber resin.		
*Note	Requires no heat, moisture, or solvent activation prior to use.		
Holding Power to Fiberboard	12,000+ min		ASTM D3654

Typical Performance Characteristics

Property	Values		Method	Substrate
Peel Adhesion	6 N/cm	55 oz/in	ASTM D3330	Stainless Steel
Elongation at Break	160 %		ASTM D3759	

Tensile Strength		Test Condition
61.3 N/cm	35 lb/in	Crosswise
122.6 N/cm	70 lb/in	Lengthwise

Property: Tensile Strength

Available Sizes

Standard Size: 4 in x 6 in

3M™ ScotchPad™ Label Protection Tape Pads 822

Handling/Application Information

Application Techniques

Sheets of 3M™ ScotchPad™ Label Protection Tape Pad 822 should be removed one at a time by grasping the liner and pulling the sheet free from the pad, holding it in a “V” form. Place the far end of the sheet down in the desired location and allow the sheet to adhere from that end back to the tabbed end. Flip out the tab and press the whole sheet flat. The ScotchPad can be stuck in a convenient place when the back sheet is peeled away and the pad is placed on a vertical surface or on a table, then only one hand is needed to dispense tape sheets for use.

Application of the ScotchPad 822 tape sheets is easiest at room temperature. At colder temperatures, approaching 32°F (0°C), the adhesive becomes more firm. Once applied, the ScotchPad 822 performs well throughout the normal temperature range typically encountered by packaged products in shipping and storage environments.

Storage and Shelf Life

To obtain best performance, use this product within 18 months from date of manufacture.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all-3m-products/-/3M-Tape-Sheets-822?N=5002385+3293242201&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=822

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/packaging. Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55106. Our fax number is 651-733-9175. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for health and safety information before using this product. For additional health and safety information, call 1-800-364-3577 or (651) 737-6501.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

