



Glass Cloth Tape

398FR • 398FRP Printed Version

Technical Data

February, 2006

Product Description

3M™ Glass Cloth Tape 398FR has an acrylic adhesive for many applications requiring high adhesion, an abrasion-resistant backing and flame retardant properties. This product is typically used for sealing aircraft cargo bay panels to provide a permanent seal.

Construction

Backing	Adhesive	Color	Liner
Glass Cloth	Acrylic	White	Blue HD Polyethylene Film

Typical Physical Properties and Performance Characteristics

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	38 oz./in. width (42 N/100 mm)	D-3330
Tensile Strength:	130 lbs./in. width (2,276 N/100 mm)	D-3759
Backing Thickness:	5.0 mils (0.13 mm)	D-3652
Total Thickness:	7.0 mils (0.18 mm)	D-3652
Elongation at Break:	7%	D-3759
Weight:	6.8 ozs./sq. yd. (231 g/m ²)	D-1000
Operational Temperature Range:	-20°F to 250°F (-29°C to 121°C)	

Features

- Meets flame retardancy requirements of F.A.R. Part 25.853(a) and F.A.R. Part 25.855(d).
- 3M™ Glass Cloth Tape 398FR meets the requirements of and can be qualified to Boeing material specification BMS 5-146 Type I, Class I, Grade A.
- **EU compliant** per directive 2003/11/EC of the European Parliament and the Council of February 6, 2003, amending Council Directive 76/769/EEC which restricts the use of penta-BDE and octa-BDE flame retardants.
- Acrylic adhesive has excellent long aging properties ideal for many permanent applications.
- White color makes finished job look appealing.
- Formulation does not contain antimony.
- High conformability.

3M™ Glass Cloth Tape

398FR • 398FRP Printed Version

Application Ideas

- Sealing thermal and acoustic insulation panels where high adhesion and flame retardancy are needed.
- Aircraft window sealing, duct sealing and seat repair.
- Protection of wire harnesses, electrical cables or hoses from temperature extremes and abrasion.
- Marine applications.
- Many general industrial uses.

Storage

Store in a clean dry place at 60-80°F (15-27°C).

Shelf Life

When stored under proper conditions, product retains its performance and properties for 24 months from date of manufacture.

Product Use

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability

Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.



Industrial Business Industrial Adhesives and Tapes Division

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

Printed in U.S.A.
©3M 2006 70-0709-5349-5 (2/06)