

August, 2019

# 3M™ Performance Plus Duct Tape Nuclear Grade 8979N

## Product Description

3M™ Performance Plus Duct Tape 8979N has a unique product construction for indoor and outdoor applications. This tape is removable with little or no adhesive residue from most opaque surfaces up to six months after application. 3M™ Performance Plus Duct Tape 8979N is also resistant to delamination and deterioration when exposed to UV outdoors for up to one year.



## Product Features

- Complies with MIL-STD-2041E(SH), Notice 1 for leachable halides, sulfur, and mercury. A certificate of analysis is included in each carton.
- Complies with ASME NQA-1 [supersedes ANSI N45.2.2 and NRC 1.38 Paragraph 2C Div A3.5 (1) (A)].
- Clean removal outdoors for up to 6 months, or indoors
- Easy to handle and apply. Moderate roll unwinding force, and tear by hand.
- Rubber adhesive bonds well to many surfaces with good initial stick.
- Moisture resistant and conformable backing.
- Strong backing with high tensile strength for demanding applications.
- Distinctive Red and Slate Blue colors available.

# 3M™ Performance Plus Duct Tape Nuclear Grade 8979N

## Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

## Typical Physical Properties

Property	Values		Method
Color	Red, Slate Blue		
Total Tape Thickness	0.3 mm	11.7 mil	ASTM D3652
Backing	Polyethylene film over cloth scrim		
Adhesive	Rubber		

## Typical Performance Characteristics

Property	Values		Method	Substrate	Notes
Peel Adhesion	5.3 N/cm	48 oz/in	ASTM D3330	Stainless Steel	
Tensile Strength	63 N/cm	576 oz/in	ASTM D3759		
Elongation at Break	19 %		ASTM D3759		
Temperature Use Range	Up to 93 °C	Up to 200 °F			
Minimum Application Temperature	4 °C	40 °F			

Table continued on next page

# 3M™ Performance Plus Duct Tape Nuclear Grade 8979N

## Typical Performance Characteristics (continued)

Property	Values		Method	Substrate	Notes
Flame Spread Index	5		ASTM E84		UL-723, NFPA 255, and UBC 8-1 are publications of the same test method.
Smoke Developed Index	0		ASTM E84		UL-723, NFPA 255, and UBC 8-1 are publications of the same test method.

## Available Sizes

Property	Values	
Standard Roll Length	54.8 m	60 yd

## Handling/Application Information

### Application Ideas

- Ideal for demanding duct tape applications in the nuclear power plant, ship building and stainless steel fabrication industries.
- Applications in the construction, electrical, industrial, marine and military markets.
- Applications for sealing, holding, identification and protection.
- Maintenance Repair and Other (MRO) applications for patching, bundling, reinforcing, tabbing and temporary repair.
- Taping and splicing insulation, capping pipe and conduit ends, marking and labeling.
- Hanging polyethylene drapes, industrial masking and light sandblast overspray protection.

### Storage and Shelf Life

Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% RH in the original carton. To obtain best performance, use this product within 24 months from date of manufacture.

# 3M™ Performance Plus Duct Tape Nuclear Grade 8979N

## Industry Specifications

MIL-STD-2041E(SH), Notice 1ASME NQA-1 [supersedes ANSI N45.2.2 and NRC 1.38 Paragraph 2C Div A3.5 (1) (A)]

## Trademarks

3M is a trademark of 3M Company.

## References

Property	Values
3m.com Product Page	<a href="https://www.3m.com/3M/en_US/company-us/all-3m-products/~/3M-Performance-Plus-Duct-Tape-8979N?N=5002385+3293242024&amp;rt=rud">https://www.3m.com/3M/en_US/company-us/all-3m-products/~/3M-Performance-Plus-Duct-Tape-8979N?N=5002385+3293242024&amp;rt=rud</a>
Safety Data Sheet (SDS)	<a href="https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&amp;msdsLocale=en_US&amp;co=ptn&amp;q=8979N">https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&amp;msdsLocale=en_US&amp;co=ptn&amp;q=8979N</a>

## ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

# 3M™ Performance Plus Duct Tape Nuclear Grade 8979N

## Information

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

**Warranty, Limited Remedy, and Disclaimer:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

**Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

# 3M™ Performance Plus Duct Tape Nuclear Grade 8979N



3M United States  
3M Center  
St. Paul, MN 55144-1000  
800-362-3550  
[www.3M.com](http://www.3M.com)

Please recycle.  
© 3M 2020. All Rights Reserved.

The brands listed above are trademarks of 3M